

RADIATOR SPECIFICATION CHART

NOTE: If your 1967 - 1970 Mustang originally came with a bolt on radiator, and you are purchasing a saddle mount radiator, you will need to buy the proper mounting brackets.

- 1967 Cars: Must use 1968 lower saddle mount brackets which are wider.

<u>Radiator</u>		<u>Height / Width</u>	<u>Inlet</u>	<u>Outlet</u>	<u>Mount</u>
251	2 - 3 - 4 Row	16 3/8" x 17 1/4"	1 1/4" diameter top right	1 1/4" diameter bottom left	Bolt on
259	3 - 4 Row	16 3/8" x 17 1/4"	1 1/2" diameter top right	1 3/4" diameter bottom right	Bolt on
329	2 - 3 Row	16 3/8" x 20 1/4"	1 1/4" diameter top right	1 1/4" diameter bottom left	Bolt on
338	2 - 3 - 4 Row	16" x 24 1/8"	1 1/2" diameter top right	1 3/4" diameter bottom right	Saddle
339	2 - 3 - 4 Row	16 3/8" x 20 1/4"	1 1/2" diameter top right	1 1/2" diameter bottom left	Bolt on
340	2 - 3 - 4 Row	16 3/8" x 20 1/4"	1 1/2" diameter top right	1 3/4" diameter bottom right	Bolt on
379	3 - 4 Row	16" x 24 1/8"	1 1/2" diameter top right	1 3/4" diameter bottom left	Saddle
381	3 - 4 Row	17 3/4" x 26"	1 1/2" diameter top right	1 1/2" - 1 3/4" diameter bottom left	Saddle
556	3 - 4 Row	17" x 24 1/2"	1 1/2" diameter top right	1 1/2" diameter bottom left	Saddle